


nokian[®]
TYRES

NOKIAN TRACTOR KING



REVOLUTIONARY FROM SURFACE TO CORE

Nokian Tractor King is a no-compromise tractor tyre for the heaviest of machinery and the most difficult terrain in forestry, earthmoving and road construction. The design from all-new tread pattern to fortified carcass is nothing short of revolutionary in a tractor tyre.



DURABILITY

Core and sidewall designed for top-class puncture-resistance in toughest conditions.

TRACTION

Wide tread and radically increased amount of tractive edges for grip on all terrains.

TAKES HEAVY LOADS

Innovatively wear-resistant tread design for comfortable, economical kilometres.

HIGH LOAD CAPACITY

Up to 320 kPa

50 % MORE TRACTIVE EDGES

Compared to conventional lug pattern

HIGH SPEED CATEGORY

65 km/h (D)



RADIAL



TUBELESS



STEEL BELTED



CCR



ARAMID SIDEWALLS



PUNCTURE PROTECTION



CHAIN USE



STUDDABLE



STONE EJECTORS



“Top-class traction and lateral grip – even on slippery rocks”

CHRISTOF WIEDERSTEIN
Hergenroth / Germany

TECHNICAL SPECIFICATIONS

| Size | LI / SS | Recommended rim | Permitted rims | Width | | Diameter | | SRI | Inflation pressure for load capacity calculation | | Load Capacity kg/lbs | | | | | | | | | | | | Max. Inflation pressure | | Product code | Available |
|-----------|---------|-----------------|-----------------------------------|-------|------|----------|------|------|--|-----|----------------------|--------|---------|--------|---------|--------|---------|--------|---------|--------|---------|-------|-------------------------|-------|--------------|-----------|
| | | | | mm | in | mm | in | | kPa | psi | 65 km/h | 40 mph | 50 km/h | 30 mph | 40 km/h | 25 mph | 30 km/h | 20 mph | 20 km/h | 10 mph | 10 km/h | 5 mph | kPa | p.s.i | | |
| 500/65R28 | 150 D | DW16L | DW15L, TW15L, TW16L, DW18L, TW18L | 503 | 19,8 | 1361 | 53,6 | 650 | 320 | 46 | 3350 | 7385 | 3520 | 7760 | 3670 | 8090 | 3850 | 8490 | 4120 | 9085 | 5030 | 11090 | 400 | 58 | T445673 | 6/2019 |
| 540/65R28 | 154 D | DW18L | DW16L, TW16L, TW18L | 550 | 21,7 | 1413 | 55,6 | 675 | 320 | 46 | 3750 | 8265 | 3940 | 8685 | 4110 | 9060 | 4310 | 9500 | 4610 | 10165 | 5630 | 12410 | 400 | 58 | T445674 | 11/2018 |
| 600/60R28 | 157 D | DW18L | TW18L, DW20B, TW20B | 601 | 23,7 | 1431 | 56,3 | 675 | 320 | 46 | 4125 | 9095 | 4330 | 9545 | 4520 | 9965 | 4740 | 10450 | 5070 | 11175 | 6190 | 13645 | 400 | 58 | T445675 | 6/2019 |
| 540/65R30 | 155 D | DW18L | DW16L, TW16L, TW18L | 550 | 21,7 | 1464 | 57,6 | 700 | 320 | 46 | 3875 | 8545 | 4070 | 8975 | 4240 | 9350 | 4460 | 9835 | 4770 | 10515 | 5810 | 12810 | 400 | 58 | T445676 | 6/2019 |
| 540/70R30 | 159 D | DW18L | DW16L, TW16L, TW18L | 540 | 21,3 | 1518 | 59,8 | 725 | 320 | 46 | 4375 | 9645 | 4590 | 10120 | 4790 | 10560 | 5030 | 11090 | 5380 | 11860 | 6560 | 14460 | 400 | 58 | T445677 | 11/2018 |
| 600/70R30 | 165 D | DW18L | TW18L, DW20B, TW20B | 591 | 23,3 | 1602 | 63,1 | 750 | 320 | 46 | 5150 | 11355 | 5410 | 11925 | 5640 | 12435 | 5920 | 13050 | 6330 | 13955 | 7730 | 17040 | 400 | 58 | T445678 | 6/2019 |
| 620/75R30 | 169 D | DW20B | TW20B | 625 | 24,6 | 1692 | 66,6 | 800 | 320 | 46 | 5800 | 12785 | 6090 | 13425 | 6350 | 14000 | 6670 | 14705 | 7130 | 15720 | 8700 | 19180 | 400 | 58 | T445679 | 6/2019 |
| 600/65R34 | 163 D | DW18L | TW18L, DW20B, TW20B | 591 | 23,3 | 1644 | 64,7 | 775 | 320 | 46 | 4875 | 10745 | 5120 | 11290 | 5340 | 11775 | 5610 | 12370 | 6000 | 13230 | 7310 | 16115 | 400 | 58 | T445680 | 11/2018 |
| 600/70R34 | 167 D | DW18L | TW18L, DW20B, TW20B | 591 | 23,3 | 1704 | 67,1 | 800 | 320 | 46 | 5450 | 12015 | 5720 | 12610 | 5970 | 13160 | 6270 | 13825 | 6700 | 14770 | 8180 | 18035 | 400 | 58 | T445681 | 11/2018 |
| 600/65R38 | 165 D | DW18L | TW18L, DW20B, TW20B | 591 | 23,3 | 1745 | 68,7 | 825 | 320 | 46 | 5150 | 11355 | 5410 | 11925 | 5640 | 12435 | 5920 | 13050 | 6330 | 13955 | 7730 | 17040 | 400 | 58 | T445682 | 6/2019 |
| 650/65R38 | 169 D | DW20B | TW20B | 645 | 25,4 | 1811 | 71,3 | 875 | 320 | 46 | 5800 | 12785 | 6090 | 13425 | 6350 | 14000 | 6670 | 14705 | 7130 | 15720 | 8700 | 19180 | 400 | 58 | T445683 | 11/2018 |
| 650/75R38 | 175 D | DW20B | TW20B, DW21B, TW21B, DW23B, TW23B | 645 | 25,4 | 1941 | 76,4 | 925 | 320 | 46 | 6900 | 15210 | 7250 | 15985 | 7560 | 16665 | 7940 | 17505 | 8490 | 18715 | 10350 | 22820 | 400 | 58 | T445684 | 11/2018 |
| 650/85R38 | 178 D | DW20B | TW20B, DW21B, TW21B, DW23B, TW23B | 645 | 25,4 | 2071 | 81,5 | 975 | 320 | 46 | 7500 | 16535 | 7880 | 17370 | 8210 | 18100 | 8630 | 19025 | 9230 | 20350 | 11250 | 24800 | 400 | 58 | T445685 | 6/2019 |
| 710/70R42 | 179 D | DW23B | TW23B, DW25B, TW25B | 716 | 28,2 | 2061 | 81,1 | 975 | 320 | 46 | 7750 | 17085 | 8140 | 17945 | 8490 | 18715 | 8910 | 19645 | 9530 | 21010 | 11630 | 25640 | 400 | 58 | T445686 | 6/2019 |
| 710/75R42 | 181 D | DW23B | TW23B, DW25B, TW25B | 716 | 28,2 | 2133 | 84 | 1025 | 320 | 46 | 8250 | 18190 | 8660 | 19090 | 9030 | 19910 | 9490 | 20920 | 10150 | 22375 | 12380 | 27295 | 400 | 58 | T445687 | 11/2018 |

In forestry or heavy road use add 40 kPa / 6 psi